

ATHENS





ATHENS

Crafted to harmonize classic sophistication with modern versatility, ATHENS Collection offers a choice between matt and polished , empowering you to redefine spaces with both style and functionality.

Drawing inspiration from the enduring beauty of ancient architecture, ATHENS balances minimalist aesthetics with intricate texture.

The matt exudes a soft, organic appeal, creating a warm, understated ambiance ideal for contemporary and Scandinavian interiors. In contrast, the polished variant reflects light dynamically, amplifying brightness and adding a touch of polished luxury perfect for modern or Art Deco-inspired settings.

Available in neutral tones and subtle veining patterns, both finishes adapt effortlessly to diverse design narratives.


Whether seeking subtle refinement or bold brilliance, ATHENS Collection merges artistic vision with resilient innovation, transforming spaces into timeless masterpieces.




ATHENS

| Matt | Lappato | Polished |


5 COLOURS



BIANCO



BONE



PERLA




GREY




DARK


3 SIZES



60×60cm
24"× 24"



60×30cm
24"× 12"



30×30cm
12"× 12"

10mm
120×60cm 48"× 24"

9mm
60×60cm 24"× 24"
60×30cm 24"× 12"
30×30cm 12"× 12"

2 FINISHES



▼ Sliptech

The soft-touch satin-finish surfaces are ideal for all interior applications as well as for new and surprising stylistic combinations.



▲ Polished

POLISHED lends elegance and style to floors and walls, allowing for enormous creativity in terms of installation patterns and colour combinations.



- Wall .
ATHENS - BIANCO
MATT
60X60cm - 24"× 24"



- Wall / Floor .
ATHENS - BIANCO
MATT
60X60cm - 24"× 24"
- Desk .
MARMO - BIANCO
MATT
60X60cm - 24"× 24"



• Wall .
ATHENS - BONE
MATT
60X60cm - 24" x 24"



• Floor .
ATHENS - BONE
POLISHED
60X60cm - 24" x 24"



• Floor .
ATHENS - PERLA
POLISHED
60X60cm - 24"× 24"



• Floor .
ATHENS - PERLA
MATT
60X60cm - 24"× 24"

- Floor .
ATHENS - GREY
POLISHED
60X60cm - 24"× 24"



- Floor .
ATHENS - DARK
MATT
60X60cm - 24"× 24"



- Floor .
ATHENS - DARK
POLISHED
60X60cm - 24"× 24"



- Wall .
ATHENS - DARK
MATT
60X60cm - 24"× 24"
- Floor .
ATHENS - GREY
MATT
60X60cm - 24"× 24"



- Floor .
ATHENS - DARK
MATT
60X60cm - 24" x 24"



ATHENS

BIANCO

PRODUCT INFORMATION

▼

9MM

▲

60×60cm/24"× 24"

6 faces

60×30cm/24"× 12"

12 faces

30×30cm/12"× 12"

24 faces

- ☒ Matt

☒ Polished



ATHENS

BONE

PRODUCT INFORMATION

▼

9MM

▲

60×60cm/24"× 24"

6 faces

60×30cm/24"× 12"

12 faces

30×30cm/12"× 12"

24 faces

- ☒ Matt

☒ Polished



ATHENS

PERLA

PRODUCT INFORMATION

▼

9MM

▲

60×60cm/24"× 24"

6 faces

60×30cm/24"× 12"

12 faces

30×30cm/12"× 12"

24 faces

- ☒ Matt

☒ Polished



ATHENS

GREY

PRODUCT INFORMATION

▼

9MM

▲

60×60cm/24"× 24"

6 faces

60×30cm/24"× 12"

12 faces

30×30cm/12"× 12"

24 faces

- ☒ Matt

☒ Polished



ATHENS DARK

PRODUCT INFORMATION

9MM

60×60cm/24"× 24"

6 faces


60×30cm/24"× 12"

12 faces

30×30cm/12"× 12"

24 faces

- ✓ Matt
- ✓ Polished






TECHNICAL SPECIFICATIONS

TECHNICAL CHARACTERISTIC	STANDARD TEST METHOD	ISO STANDARD REQUIREMENT	OUR VALUES
Length & Width	ISO 10545-2	±0.6%Max	±0.3%Max
Thickness	ISO 10545-2	±5.0%Max	±5.0%Max
Sides Straightness	ISO 10545-2	±5.0%Max	±0.25%Max
Rectangularity	ISO 10545-2	±0.5%Max	±0.25%Max
Flatness: a) Centre Curvature b) Edge Curvature c) Warpage	ISO 10545-2 ISO 10545-2 ISO 10545-2	±0.5%Max ±0.5%Max ±0.5%Max	±0.2%Max/Max2.0mm ±0.2%Max/Max2.0mm ±0.2%Max/Max2.0mm
Surface Quality	ISO 10545-2	≥ 95%FREE From visible defect	Comply
Water Absorption	ISO 10545-3	≤ 0.5%	≤ 0.20%
Breaking Strength	ISO 10545-4	≥ 1300N	≥ 1300N
Modulus Of Rupture	ISO 10545-4	≥ 35N/mm ² Individual ≥ 32N/mm ²	≥ 35N/mm ² Individual ≥ 32N/mm ²
Abrasion Resistance a) Deep Abrasion For Unglazed Tiles b) Surfaces Abrasion For Glazed Tiles	ISO 10545-6 ISO 10545-7	≤ 175mm ³ Manuf.to state abrasion class,cycie and passed	≤ 160mm ³ ≥ PEI 3 (Dependent On Product Type)
Crazing Test (glazed Tiles)	ISO 10545-11	No Sign Of Crazing	No Sign Of Crazing
Frost Resistance	ISO 10545-12	Required	No Visible Crack
Chemical Resistance a) low concentrations b) household chemicalais and Swimming pool salts	ISO 10545-13 ISO 10545-13	Manuf. to state ≥ class B	Class A Class B(For Polished Tiles) Class A Class B(For Polished Tiles)
Stain Resistance a) for unglazed tiles b) for glazed tiles	ISO 10545-14 ISO 10545-14	Manuf. to state ≥ class 3	≥ Class 3 ≥ Class 3
Slip Resistance (Excluding Polished, Lappato And Satin Finishing)	AS/NZS 4586 App.A	Manuf. to state	Wet Pendulum ≥ P4 (Dependent On Product Type)

PACKING SPECIFICATIONS

SERIES	SIZES	PCS/CTN	m ² /CTN	KG/CTN	m ² /PLT	KG/PLT	CTN/PLT
ATHENS	60x60 / 24"x24"	4	1.44	30	57.60	1200	40
	30x60 / 12"x24"	8	1.44	30	57.60	1200	40
	30x30 / 12"x12"	16	1.44	30	57.60	1200	40





Foshan Casagres International Co, Ltd.
info@casagresintl.com
www.casagresintl.com